

SAFETY DATA SHEET MAXIMA 5W-40

Prepared according to Annex II of EC regulation 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	MAXIMA 5W-40
SUPPLIER	OMV PETROL OFİSİ A.Ş.
	Ayazağa Eski Büyükdere Cad.
	No:33-37 B Blok 34398
	Maslak-Istanbul/TURKEY
	Tel: +90 212 329 1500
	Fax: +90 212 329 1896
	www.poas.com.tr
	info@poas.com.tr
PRODUCT NO.	11172
APPLICATION	Engine oil
EMERGENCY TELEPHONE	POAŞ: +90 212 329 1845 (office hours)

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
Calcium branched chain alkyl phenate sulfide	291-829-9		1-5%	R53.
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC; BASEOIL - U (DMSO <%3 by IP 346)	265-157-1	64742-54-7	60-100%	-
Polyalkyl arylamine			< 1%	N;R51/53.
Zinc alkyldithiophosphate	272-028-3	68649-42-3	1-5%	Xi;R38,R41. N;R51/53.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Get medical attention if any discomfort continues.

NOTES TO THE PHYSICIAN

No specific treatment.treat symptomatically.

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

MAXIMA 5W-40

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Keep run-off water out of sewers and water sources. Dike for water control.

SPECIFIC HAZARDS

In case of fire, toxic gases may be formed (COx, NOx).

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT





ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES APPEARANCE Liquid COLOUR Brown RELATIVE DENSITY 0.86 g/ml 15 VISCOSITY FLASH POINT (°C) 230 OC (Open cup).

10 STABILITY AND REACTIVITY

MAXIMA 5W-40

STABILITY

Stable under normal temperature conditions. **CONDITIONS TO AVOID** Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidisers. **HAZARDOUS DECOMPOSITION PRODUCTS** Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Liquid may irritate skin.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

The packaging must be empty (drop-free, when inverted)

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Environmental manager must be informed of all major spillages. Do not allow runoff to sewer, waterway or ground.

14 TRANSPORT INFORMATION

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).
	No transport warning sign required.
ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not classified.
SEA TRANSPORT NOTES	Not classified.
AIR TRANSPORT NOTES	Not classified.

15 REGULATORY INFORMATION

RISK PHRASES

NC

Not classified.

SAFETY PHRASES

Safety data sheet available for professional user on request.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

P13

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

INFORMATION SOURCES

This SDS is prepared based on the information received from raw material suppliers.

MAXIMA 5W-40

REVISION COMMENTS

Company name changed				
ISSUED BY				
Certificated from the Turkish Standards Institute (TSE) to prepare Safety Data Sheet (Certificate no: SDS - 0397)				
REVISION DATE	17.06.2011			
DATE	24.09.2010			
RISK PHRASES IN FULL				
NC	Not classified.			
R38	Irritating to skin.			
D44	Diale of equipue demonstrate even			

R41 Risk of serious damage to eyes.

R51/53Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.R53May cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.