

## SAFETY DATA SHEET DENIZ DIZEL 3000 SAE 40

Prepared according to Annex II of EC regulation 1907/2006

# 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME

DENIZ DIZEL 3000 SAE 40

SUPPLIER

OMV PETROL OFISI A.Ş.

Ayazağa Eski Büyükdere Cad. No:33-37 B Blok 34398 Maslak-Istanbul/TURKEY Tel: +90 212 329 1500 Fax: +90 212 329 1896 www.poas.com.tr

info@poas.com.tr

PRODUCT NO. 11425

APPLICATION Marine Lubricant

EMERGENCY TELEPHONE POAŞ: +90 212 329 1845 (office hours)

### **2 HAZARDS IDENTIFICATION**

Not regarded as a health or environmental hazard under current legislation.

### **ENVIRONMENT**

The product is not expected to be hazardous to the environment.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
Calcium branched chain alkyl phenate sulfide	291-829-9		5-10%	R53.
ETHANEDIOL	203-473-3	107-21-1	< 1%	Xn;R22
HYDROCARBONS, C20-50, SOLVENT DEWAXED HEAVY PARAFFINIC, HYDROTREATE (DMSO<3% by IP 346)	292-617-9	90640-95-2	60-100%	-
Polyolefin polyamine succinimide			< 1%	R53.
Zinc alkyldithiophosphate	272-028-3	68649-42-3	< 1%	Xi;R38,R41. N;R51/53.

The Full Text for all R-Phrases are Displayed in Section 16

### **COMPOSITION COMMENTS**

Some substances are not classified by legistlation. They are self classified by the manufacturer. The DMSO extract by IP 346 of the oil is less than 3%

### **4 FIRST-AID MEASURES**

### **GENERAL INFORMATION**

Get medical attention if any discomfort continues.

### **INHALATION**

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

### INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

### **DENIZ DIZEL 3000 SAE 40**

#### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

### **EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### **5 FIRE-FIGHTING MEASURES**

### **EXTINGUISHING MEDIA**

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

### SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

### **6 ACCIDENTAL RELEASE MEASURES**

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### **ENVIRONMENTAL PRECAUTIONS**

Do not discharge into drains, water courses or onto the ground.

### SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

### 7 HANDLING AND STORAGE

### **USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container.

### **8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
ETHANEDIOL	WEL		52 mg/m3(Sk)		104 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

### PROTECTIVE EQUIPMENT







### **ENGINEERING MEASURES**

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

### HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

### **EYE PROTECTION**

If risk of splashing, wear safety goggles or face shield.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### **DENIZ DIZEL 3000 SAE 40**

### **HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid
COLOUR Yellow

ODOUR Characteristic.

**RELATIVE DENSITY** 0.91 g/ml 15 **VISCOSITY** 9.3-12.5 cSt 100

FLASH POINT (°C) 270 OC (Open cup).

### 10 STABILITY AND REACTIVITY

### **STABILITY**

Stable under normal temperature conditions.

### **CONDITIONS TO AVOID**

Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidisers.

### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

### 11 TOXICOLOGICAL INFORMATION

### INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

#### **INGESTION**

May cause discomfort if swallowed.

### SKIN CONTACT

Liquid may irritate skin.

### **EYE CONTACT**

Spray and vapour in the eyes may cause irritation and smarting.

### 12 ECOLOGICAL INFORMATION

### **ECOTOXICITY**

Not regarded as dangerous for the environment.

### 13 DISPOSAL CONSIDERATIONS

### **DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

### 14 TRANSPORT INFORMATION

**GENERAL** The product is not covered by international regulation on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

No transport warning sign required.

ROAD TRANSPORT NOTES Not classified.

SEA TRANSPORT NOTES Not classified.

AIR TRANSPORT NOTES Not classified.

Not classified.

### 15 REGULATORY INFORMATION

**RISK PHRASES** 

NC Not classified.

SAFETY PHRASES

NC Not classified.

### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

### **DENIZ DIZEL 3000 SAE 40**

### APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

### **GUIDANCE NOTES**

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

### **16 OTHER INFORMATION**

### INFORMATION SOURCES

This SDS is prepared based on the information received from raw material suppliers.

### **REVISION COMMENTS**

Company name changed

**ISSUED BY** 

Certificated from the Turkish Standards Institute (TSE) to prepare Safety Data Sheet (Certificate no: SDS - 0397)

**REVISION DATE** 20.06.2011 **DATE** 28.09.2010

**RISK PHRASES IN FULL** 

R22 Harmful if swallowed.
R38 Irritating to skin.

R53 May cause long-term adverse effects in the aquatic environment.

NC Not classified.

R41 Risk of serious damage to eyes.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.