

# SAFETY DATA SHEET CARIUS EP 220

Prepared according to Annex II of EC regulation 1907/2006

# 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	CARIUS EP 220
SUPPLIER	OMV PETROL OFİSİ A.Ş.
	Ayazağa Eski Büyükdere Cad.
	No:33-37 B Blok 34398
	Maslak-Istanbul/TURKEY
	Tel: +90 212 329 1500
	Fax: +90 212 329 1896
	www.poas.com.tr
	info@poas.com.tr
PRODUCT NO.	43161
APPLICATION	Grease
EMERGENCY TELEPHONE	POAŞ: +90 212 329 1845 (office hours)

# **2 HAZARDS IDENTIFICATION**

Irritating to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **CLASSIFICATION (1999/45)** Xi;R36. R52/53.

#### ENVIRONMENT

The product contains a substance which is harmful to aquatic organisms.

#### PHYSICAL AND CHEMICAL HAZARDS

This product is not flammable.

# **3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification (67/548)
12 Hydroxy Stearic Acid		106-14-9	5-10%	-
Alkyl phosphate			< 1%	C;R34.
DIPHENYLAMINE	204-539-4	122-39-4	< 1%	T;R23/24/25 R33 N;R50/53
Lithium Hydroxide, Monohydrate			1-5%	C;R34. Xi;R37.
Long chain alkenyl amine			< 1%	Xn;R22. C;R35. N;R50.
Long chain alkyl amine			< 1%	T;R23/24. Xn;R22,R48/20. C;R34. N;R50/53. R43.
Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)	278-012-2	74869-22-0	60-100%	-
Zinc alkyldithiophosphate	272-028-3	68649-42-3	1-5%	Xi;R38,R41. N;R51/53.

The Full Text for all R-Phrases are Displayed in Section 16

#### COMPOSITION COMMENTS

Some substances are not classified by legistlation. They are self classified by the manufacturer. The DMSO extract by IP 346 of the oil is less than 3%

## **4 FIRST-AID MEASURES**

## GENERAL INFORMATION

Get medical attention if any discomfort continues.

#### INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

## INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

## SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

## EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

# 5 FIRE-FIGHTING MEASURES

## **EXTINGUISHING MEDIA**

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours.

## PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

# **6 ACCIDENTAL RELEASE MEASURES**

#### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

#### **ENVIRONMENTAL PRECAUTIONS**

Do not discharge into drains, water courses or onto the ground.

#### SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

## **7 HANDLING AND STORAGE**

#### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

#### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container.

## STORAGE CLASS

Chemical storage.

# 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA	- 8 hrs	STEL	- 15 min	Notes
DIPHENYLAMINE	WEL		10 mg/m3		20 mg/m3	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS WEL = Workplace Exposure Limits PROTECTIVE EQUIPMENT



## PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

#### **RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

#### HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

#### EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

#### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

#### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## **9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Grease
COLOUR	Blue
ODOUR	Characteristic.
RELATIVE DENSITY	İşlenmiş Penetrasyon/ Worked Penetration: 265-295 25

# **10 STABILITY AND REACTIVITY**

#### STABILITY

Stable under normal temperature conditions.

#### CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time. Avoid contact with oxidisers or reducing agents.

#### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

## **11 TOXICOLOGICAL INFORMATION**

#### INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

#### INGESTION

May cause discomfort if swallowed.

#### SKIN CONTACT

Liquid may irritate skin.

#### EYE CONTACT

Irritating to eyes.

# 12 ECOLOGICAL INFORMATION

## ECOTOXICITY

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 13 DISPOSAL CONSIDERATIONS

#### **DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

## **14 TRANSPORT INFORMATION**

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).
	No transport warning sign required.
ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not classified.

# SEA TRANSPORT NOTES AIR TRANSPORT NOTES

Not classified. Not classified.

# **15 REGULATORY INFORMATION**

# LABELLING



Irritan **RISK PHRASES** R36 Irritating to eyes. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. SAFETY PHRASES S2 Keep out of the reach of children. S25 Avoid contact with eyes. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S46 If swallowed, seek medical advice immediately and show this container or label. S56 Dispose of this material and its container to hazardous or special waste collection point. S64 If swallowed, rinse mouth with water (only if the person is conscious). P14 Contains Long chain alkyl amine. May produce an allergic reaction.

# STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

## APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### **GUIDANCE NOTES**

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

# **16 OTHER INFORMATION**

#### **REVISION COMMENTS**

 Company name changed

 ISSUED BY

 Certificated from the Turkish Standards Institute (TSE) to prepare Safety Data Sheet (Certificate no: SDS - 0397)

 REVISION DATE
 13.06.2011

 DATE
 26.02.2011

#### **RISK PHRASES IN FULL**

R34	Causes burns.
R35	Causes severe burns.
R33	Danger of cumulative effects.
R22	Harmful if swallowed.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
NC	Not classified.
R41	Risk of serious damage to eyes.
R23/24	Toxic by inhalation and in contact with skin.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R50	Very toxic to aquatic organisms.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.