

SAFETY DATA SHEET MAXIMUS TURBO DIESEL S 15W-40

Prepared according to Annex II of EC regulation 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME MAXIMUS TURBO DIESEL S 15W-40

SUPPLIER OMV PETROL OFISI A.Ş.

Ayazağa Eski Büyükdere Cad. No:33-37 B Blok 34398 Maslak-Istanbul/TURKEY Tel: +90 212 329 1500 Fax: +90 212 329 1896 www.poas.com.tr

info@poas.com.tr

PRODUCT NO. 11344

APPLICATION Engine oil

EMERGENCY TELEPHONE POAŞ: +90 212 329 1845 (office hours)

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
Alkoxylated long chain alkyl alcohol			< 1%	Xi;R41. N;R50.
Calcium long chain alkaryl sulfonate			< 1%	Xi;R38.
Calcium long chain alkylphenate sulfide			< 1%	R53.
Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)	278-012-2	74869-22-0	60-100%	-
p-dodecylphenol	310-154-3	121158-58-5	< 1%	Repr. Cat. 3;R62. Xi;R38. N;R50/53.
Zinc alkyldithiophosphate	272-028-3	68649-42-3	1-5%	Xi;R38,R41. N;R51/53.

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Some substances are not classified by legistlation. They are self classified by the manufacturer. The DMSO extract by IP 346 of the oil is less than 3%

4 FIRST-AID MEASURES

GENERAL INFORMATION

Get medical attention if any discomfort continues.

NOTES TO THE PHYSICIAN

No specific treatment.treat symptomatically.

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

REVISION DATE: 17.06.2011

MAXIMUS TURBO DIESEL S 15W-40

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Fire can be extinguished using: Foam, carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Keep run-off water out of sewers and water sources. Dike for water control.

SPECIFIC HAZARDS

In case of fire, toxic gases may be formed (COx, NOx).

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT







ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact. Use protective gloves made of: Nitrile. Polyvinyl chloride (PVC).

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

REVISION DATE: 17.06.2011

MAXIMUS TURBO DIESEL S 15W-40

APPEARANCE Liquid COLOUR Brown

RELATIVE DENSITY 0.88 g/ml 15 **VISCOSITY** 15-16.3 cSt 100

FLASH POINT (°C) 228 OC (Open cup).

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidisers.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Liquid may irritate skin.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

The packaging must be empty (drop-free, when inverted)

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Environmental manager must be informed of all major spillages. Do not allow runoff to sewer, waterway or ground.

14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

No transport warning sign required.

ROAD TRANSPORT NOTES Not Classified.

RAIL TRANSPORT NOTES Not classified.

SEA TRANSPORT NOTES Not classified.

AIR TRANSPORT NOTES Not classified.

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

P13 Safety data sheet available for professional user on request.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

REVISION DATE: 17.06.2011

MAXIMUS TURBO DIESEL S 15W-40

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

INFORMATION SOURCES

This SDS is prepared based on the information received from raw material suppliers.

REVISION COMMENTS

Company name changed

ISSUED BY

Certificated from the Turkish Standards Institute (TSE) to prepare Safety Data Sheet (Certificate no: SDS - 0397)

REVISION DATE 17.06.2011 **DATE** 30.03.2011

RISK PHRASES IN FULL

NC Not classified.
R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R50 Very toxic to aquatic organisms.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53 May cause long-term adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.