

ATF CVT

Synthetic CVT Automatic Transmission Fluid

Definition

PO ATF CVT is a transmission oil suitable for CVT type automatic transmissions working with belt and chain drive method.

Places of Use

It can be used in the following applications:

Chrysler Jeep NS-2

Dodge CVTF + 4

Honda HCF2

Hyundai SP-III

Mini Cooper EZL799

Mitsubishi SP-III

Nissan NS-1

Nissan NS-3

Subaru iCVT

Suzuki CVTF TC

Toyota CVTF FE

• Daihatsu Ammix CVT • Nissan NS-2

GM Dex-CVT

Honda HMMF * 1)

• JASO 1A capable

Mitsubishi CVTF-J1

Subaru ECVT

Suzuki CVT Green 1

Suzuki NS-2

Toyota CVTF TC

Features and Benefits

- Smooth driving comfort with its improved friction regulator feature

Safe driving

Longer equipment life

- Extended service interval

- High seal and seal compatibility

Typical Features *

Density, @ 15 ° C, kg / m ³ Flash	ASTM D 4052	0.844
Point, COC, ° C Viscosity, 40 ° C,	ASTM D 92	230
mm ² / s Viscosity, 100 ° C, mm ² /	ASTM D 445	37
s Viscosity Index	ASTM D 2270	182
Pour Point, ° C	ASTM D 97	- 42

* Values may differ from production to production.



Petrol Ofisi