

MAXIMA AUTO LPG 5W-30

Synthetic Motor Oil for New Generation LPG Fueled Engines

Definition

It is a synthetic engine oil specially formulated for LPG vehicles, produced by adding high performance additives to high technology synthetic base oils.

Places of Use

It can be used in passenger cars and light commercial vehicles with LPG fuel conversion with a new generation engine and vehicles with factory installed LPG fuel system.

Features and Benefits

- Prevents overheating caused by overheating arising in engines operating with LPG.
- Resistant to high engine temperature thanks to its synthetic formula.
- With its special formula, it provides reduction control with less evaporation loss. It minimizes the abrasion by reducing the friction during the first operation.
- Extends engine life by providing superior protection against wear and corrosion.
- Increases engine efficiency, provides high engine power.
- Provides faster start-up and protection.

Specifications and Approvals

API SL / CF, ACEA A3 / B4

Typical Features *

SAE Viscosity Grade		5W-30
Density, @ 15 ° C, kg / m ³ Flash	ASTM D-4052	0.853
Point, COC, ° C Viscosity, 40 ° C,	ASTM D-92	230
mm ² / s Viscosity, 100 ° C, mm ² /	ASTM D 445	67,2
s Viscosity Index		11.9
	ASTM D-2270	160
Pour Point, ° C	ASTM D-97	- 41

* Values may differ from production to production.