

Özel Antifriz

Ethylene Glycol Based Special Antifreeze

Description

It is high quality oil with long service life, containing special additives in the ethylene base substance. It does not contain amine and phosphate.

Application

It is used all engine cooling system. against freezing, boiling, corrosion, rusting, cavitation and wearing out. It might be added into the cooling system that contains ethylene base antifreeze.

Benefits

- Provides perfect protection of the engine cooling system against freezing, boiling, corrosion, rusting, cavitation and wearing out.
- It does not evaporate at radiator temperatures.
- The cooling system should not be contaminated and leak-free, should the result be perfect.
- Only clean and clear water should be used.
- It might be added into the cooling system that contains ethylene base antifreeze.

Performance

MAN 324 Type NF, MB 325.0, ZF INTARDER, BMW N 600 69.0, AUDI TL 774-C, PORSCHE 774 C, VW TL 774 C, CAT SEBU 6250-12, MTU MTL 5048, JENBACHER, SKODA, SEAT, OPEL

Typical Specifications*

Density, @ 15°C g/ml	ASTM 4052	1.12
Flash Point COC, °C	ASTM D 92	126
Freezing Point, °C		
%50+Water	ASTM D 1177	-38
%33+Water		-18
Boiling Point, °C	ASTM D 1120	158
%100	ASTMIDITZU	136
pH, 20°C		
%100	ASTM D 1287	7.24
%30		8.4

^{*} Values are changeable according to production.

Packing

	Drum	200 kg
--	------	--------

