

MAXIMA CX 5W-30

Fully Synthetic Engine Oil for Particulate Filter Vehicles

Definition

It is a new generation engine oil formulated with synthetic base oils and special additives, produced for vehicles with emission reduction systems containing DPF and SCR.

Places of Use

Maxima CX 5W-30; It can be used in diesel passenger cars and light commercial vehicles equipped with DPF and SCR exhaust systems requiring ACEA C2 or C3 performance level engine oil and gasoline vehicles with catalytic converters.

Features and Benefits

- Provides product optimization in large vehicles consisting of different brands.
- Provides high engine performance.
- Extends the life of exhaust emission systems.
- It protects the environment by contributing to the production of low emissions.
- It keeps the engine clean by reducing deposit and deposit formation.
- Helps fuel saving.

Specifications and Approvals

ACEA C2 / C3-12, API SN, MB-APPROVAL 229.31, FIAT 9.55535-S1

Typical Features *

SAE Viscosity Grade		5W-30
Density, @ 15 ° C, kg / m ³ Flash	ASTM D-4052	0.849
Point, COC, ° C Viscosity, 40 ° C,	ASTM D-92	220
mm ² / s Viscosity, 100 ° C, mm ² /	ASTM D 445	74,7
s Viscosity Index		12,4
	ASTM D-2270	165
Pour Point, ° C	ASTM D-97	- 33

* Values may differ from production to production.

