



## Super Gres EP

### Description

It is a multi-purpose soap grease, supplemented by excessive pressure additive.

### Application

It is used in operations where excessive impact loads are present. Type 0 is used especially for high-speed applications with capillary tubes in the presence of the water in the winter, whereas type 1 and 2 are used during summer. Type 2 is recommended for especially wide roller bearings at the dry and wet ends of the paper machines. It is suitable for operation between -12 to 130 °C.

### Benefits

- Provides excellent protection under severe and impact loading, thanks to its high-pressure resistance property.
- Extends ball bearings' service life by minimizing the wear and aging.
- Ensures economy in material by reducing the need of grease.
- Reduces the cost of maintenance and labor.
- Suitable to pumping via central lubricating systems.
- Provides excellent protection against rusting and corrosion.

### Performance

MAN 283 Li-P2, Li-12 HSA, 50 lb Timken

### Typical Specifications\*

NLGI	-	0	1	2	3
Soap Type	-	Lithium	Lithium	Lithium	Lithium
Penetration 25°C, worked	ASTM D-217	365	325	268	235
Timken OK, 50 lb	ASTM D-2509	Pass	Pass	Pass	Pass
Drop Point, °C	ASTM D-566	200	200	200	200

\* Values are changeable according to production.

### Packing

Tin Can	16 kg
Drum	180 kg

