



# maxima diesel LA 5W-30

Fully Synthetic Motor Oil for  
Vehicle with Diesel Particulate Filter

## Description

maxima Diesel LA 5W-30 is a low-ash, synthetic motor oil for up-to-date gasoline and diesel engines with particulate filter. It offers high reliability and allows maximum reduction of fuel consumption.

## Applications

Can be used in high performance passenger cars which are gasoline and diesel engines with particulate filter.

## Benefits

- Thanks to the low-ash additives it contains, it ensures superior engine protection and longer oil change intervals.
- Long durability of particulate filter.
- Helps protect the environment by lowering exhaust emission.
- Avoids wears especially during warm-up phase.
- Keeps the engine clean.
- Extends service life for batteries by providing easy start-up even at low temperatures.

## Performance

API SN, ACEAC3 MB-Approval 229.51, MB 229.52, BMW LL-04, FIAT 9.55535-52

## Typical Specifications\*

|                              |             |       |
|------------------------------|-------------|-------|
| SAE Viscosity Grade          |             | 5W-30 |
| Density, @ 15°C g/ml         | ASTM 4052   | 0,85  |
| Flash Point, COC, °C         | ASTM D 92   | 228   |
| Kinematic Viscosity,         |             |       |
| at 40°C, mm <sup>2</sup> /s  | ASTM D 445  | 60,4  |
| at 100°C, mm <sup>2</sup> /s |             | 11,2  |
| Viscosity Index              | ASTM D 2270 | 181   |
| Pour Point, °C               | ASTM D 97   | -33   |

\* Values shown may differ between productions.

