



maxima
DIZEL & BENZİN GA 5W-30

Fully Synthetic Motor Oil

Description

maxima GA 5W-30 is a fully synthetic engine oil developed for diesel and gasoline engines with particulate filter. It is recommended in particular for use in Opel, BMW and Mercedes-Benz vehicles which require the use of engine oils produced with low-ash technology. It has official GM dexos2™ approval.

Applications

Recommended for high performance gasoline and diesel passenger cars and light commercial vehicles. It is particularly well suited for Opel cars where dexos2™ performance level is a requirement.

Benefits

- The low ash, phosphorus and sulphur contents extend the life of exhaust systems, and protects the environment.
- It keeps the engine clean, decreases friction, and extends the life of the engine.
- It provides excellent wear control, in particular during starts.
- It provides fuel savings up to 3%.

Performance

API SN, ACEA A3/B4/C3, GM dexos2, VW 502.00/505.00/505.01, MB 229.51, MB 229.52

Typical Specifications*

SAE Viscosity Category		5W-30
Density, @ 15°C g/ml	ASTM D 4052	0,85
Flash Point, COC, °C	ASTM D 92	228
Kinematic Viscosity, at 40°C, mm ² /s	ASTM D 445	60,36
at 100°C, mm ² /s		11,2
Viscosity Index	ASTM D 2270	181
T.B.N, mgKOH/gr	ASTM D 2896	7
Pour Point, °C	ASTM D 97	-33

* Values shown may differ between productions.

