

## MAXIMA K 5W-40

Fully Synthetic Gasoline Engine Oil

### Definition

It is a new generation engine oil formulated with synthetic base oils and special additives, produced for vehicle engines with emission reduction systems containing DPF and SCR.

### Places of Use

Maxima K 5W-40; It can be used in diesel passenger cars equipped with DPF and SCR exhaust emission systems, light commercial vehicles and gasoline vehicle engines with catalytic converters requiring ACEA C3 performance level engine oil. It is recommended not to use any additives with this oil. Specially developed for KIA branded vehicles.

### Features and Benefits

- Provides excellent protection even in fast, harsh and high temperature operating conditions.
- Provides maximum fuel saving, keeps the engine clean.
- It slows the aging of the oil by providing a longer oil change interval.
- Provides high engine power by reducing friction inside the engine.
- Provides excellent oxidation resistance.

### Specifications and Approvals

ACEA C3, API SN

### Typical Features \*

SAE Viscosity Grade		5W-40
Density, @ 15 ° C, kg / m <sup>3</sup> Flash	ASTM D-4052	0.85
Point, COC, ° C Viscosity, 40 ° C,	ASTM D-92	240
mm <sup>2</sup> / s Viscosity, 100 ° C, mm <sup>2</sup> /	ASTM D 445	81,5
s Viscosity Index		13,6
	ASTM D-2270	171
Pour Point, ° C	ASTM D-97	- 36

\* Values may differ from production to production.