



maxima
DIZEL & BENZİN
0W-20

Fully Synthetic Motor Oil

Description

maxima 0W-20 is produced based on synthetic lubrication technology to fulfill expectation of new high technology engines.

Applications

maxima 0W-20 is recommended for the vehicles requiring special lubricants, designed specifically for improved engine performance, increased fuel efficiency and engine deposits.

Benefits

- Extends drain intervals far beyond those recommended for conventional oils.
- Maximizes energy efficiency for improved fuel economy.
- maxima 0W-20 motor oil provides outstanding anti-wear protection with excellent viscosity film strength.
- Low-viscosity lubrication ensures improved engine performance through a wide range of temperatures. Especially in cold weather, quick flow to critical parts will result in faster starts and better overall engine protection.

Performance

API SN/CF, ACEA A1/B1

Typical Specifications*

SAE Viscosity Grade		0W-20
Density, @ 15°C kg/lt	ASTM D 4052	0,85
Flash Point, COC, °C	ASTM D 92	228
Kinematic Viscosity,		
at 40°C, mm ² /s	ASTM D 445	45,5
at 100°C, mm ² /s		8,8
Viscosity Index	ASTM D 2270	177
T.B.N, mgKOH/gr	ASTM D 2896	6,8
Pour Point, °C	ASTM D 97	-30

* Values shown may differ between productions.

