



## maximoto 2T

### 2-Cycle, Air Cooled High Quality Engine Oil

#### Description

It is high quality oil produced for 2-cycle engines by special pack of additives to quality paraffinic base oils.

#### Application

It can be used in all types of 2-stroke motorcycle and scotter air-cooled engines. In general, oil to fuel ratio ranges between 1/16 to 1/50. It is recommend to examine Original Equipment Manufacturer booklet for suitable raito ranges.

#### Oil to fuel ratio ranges

Ratio Ranges is recommend by OEM	Oil Quantity which is mixed every 4 lt. Fuel
1:10	400 ml
1:15	265 ml
1:20	200 ml
1:25	160 ml
1:30	135 ml
1:40	100 ml
1:50	80 ml

#### Benefits

- It minimizes the residue formation, thanks to its detergent-dispersing additive contents and conveys the wastes to the exhaust gases.
- Helps protect the environment by lowering exhaust emission.
- It prevents water and vapor leakage, thanks to the formation of the film layer of rust preventive additives on the metallic surfaces and thus prevents rusting.
- It contributes to the prevention of the piston and cylinder wears and rings distortion thanks to its additive contents improves pre-combustion.

#### Performance

API TC, (CEC TSC-3)

#### Typical Specifications\*

Density, 15°C g/ml	ASTM 4052	0.89
Flash Point, COC, °C	ASTM D 92	250
Kinematic Viscosity at 40 °C mm <sup>2</sup> /s at 100 °C mm <sup>2</sup> /s	ASTM D 445	128.92 13.21
Viscosity Index	ASTM D 2270	95
Pour Point, °C	ASTM D 97	-12

\* Values are changeable according to production.

#### Packing

Plastic	1 lt, 1/2 lt
Drum	180 kg

