



maximoto 10W-40

4 Stroke Synthetic Motorcycle Engine Oil

Description

Maximoto 10W-40 is a high performance and high quality synthetic 4 stroke motorcycle engine oil which is produced smart oil technology.

Application

It is used 4 stroke and high performance, either liquid or air cooled motorcycles all around year. In addition, European and Japanese motorcycle manufacturers which are suitable API SG and/or JASO MA specification.

Benefits

- Thanks to Intelligent Oil Technology which is mixture of Synthetic baseoil and additives;
- Improves service life due to superior engine protective feature.
 - It prevents the engine against rusting, corrosion and foaming.
 - Ensures high and stable viscosity index.
 - Ensures the operation of the engine in a wide range of operation temperature.
 - Effective all-year-round suitability even under adverse conditions such as very low temperatures for starting or very high ambient temperatures.
 - Ensures good cold start properties.
 - Reduces the necessity of frequent oil replacements.

Performance

API SG, JASO MA

Typical Specifications*

SAE Viscosity Grade		10W-40
Density, @ 15°C g/ml	ASTM 4052	0.873
Flash Point, COC, °C	ASTM D 92	210
Kinematic Viscosity at 40 °C mm ² /s at 100 °C mm ² /s	ASTM D 445	101 15
Viscosity Index	ASTM D 2270	156
Pour Point, °C	ASTM D 97	-30

* Values are changeable according to production.

Packing

Plastic Bottles	1 lt
Drum	180 kg

