

Maxitrak Traktör Yağı 15W-40

Multigrade Tractor Engine Oil

Description

It is a high performance and superior quality multi-grade diesel engine oil produced by addition of additives package to high tech paraffinic base oils that can be used of all the year round.

Application

It is used new generation modern tractor, agricultural equipment including the latest models and diesel engines with heavy-duty vehicles

Benefits

- It cleans the engine by preventing the formation of deposits and residues under hot and cold temperatures, thanks to its detergent-dispersing additive contents.
- It promotes cold starting and effective lubrication under hot temperatures.
- No oil loss, pressure loss and foaming are observed even under severe conditions.
- It prevents corrosion by neutralizing the acids formed even during combustion.
- It forms thick oil film even at elevated temperatures, thanks to its high viscosity index and additives against wear.
- It minimizes engine wear.
- It minimizes formation of deposits; it enhances the combustion efficiency by keeping the engine clean.
- Helps protect the environment by lowering exhaust emission.
- It extends the oil replacement intervals.

Performance

API CF-4 / CF

Typical specifications*

SAE Viscosity Grade		15W-40
Density, 15°C g/ml	ASTM 4052	0.886
Flash Point, COC, °C	ASTM D 92	234
Kinematic Viscosity at 40 °C mm²/s at 100 °C mm²/s	ASTM D 445	116.54 15.44
Viscosity Index	ASTM D 2270	139
Pour Point, °C	ASTM D 97	-30

^{*} Values are changeable according to production.

Packing

Plastic	17.5 kg, 10 lt
Drum	180 kg



