



MAXIMUS Turbo Diesel S 15W-40

High Performance Heavy Duty Diesel Engine Oil

Description

A high quality diesel engine oil. Ensures high performance in all diesel engines operating under heavy service conditions thanks to its superior protection and long service life characteristics.

Application

Recommended for all applications involving trucks, buses, construction machinery, agricultural machinery and generators equipped with a diesel engine, especially with a turbocharged engine.

Benefits

- It prevents formation of deposits and residue, thanks to its detergent-dispersing type additive package content.
- It prevents wear during cold starting.
- It provides the utmost result by preventing the engine to use fuel with high sulfur content, thanks to its high TBN value.
- It extends the oil replacement intervals.
- It has an excellent highway and construction works performance.
- It prevents pressure loss and minimizes oil evaporation.

Performance

API CF-4/CF/SH, ACEA E2, MB 228.1, MAN 271, MIL-L 2104 E

Typical Specifications*

SAE Viscosity Grade		15W-40
Density, @ 15°C g/ml	ASTM 4052	0.885
Flash Point , COC, °C	ASTM D 92	232
Kinematic Viscosity at 40°C mm ² /s	ASTM D 445	116.3
at 100°C mm ² /s		15,7
Viscosity Index	ASTM D 2270	143
Pour Point, °C	ASTM D 97	-27

* Values are changeable according to production.

Packing

Plastic Bottles	1 lt, 3 lt, 4 lt, 7 lt, 17.5 kg
Tin Can	16 kg
Drum	180 kg

