



MAXIMUS XT 10W-40

High Performance, Synthetic, Heavy Duty Diesel Engine Oil

Description

Produced with synthetic technology for heavy duty diesel engine oil. Extreme performance for diesel engines which are using low or high sulfur content diesel fuel.

Applications

It is recommend for turbocharged and low emuissioned diesel engines and all of truck, bus, long way transportation, construction machines and generators. MAXIMUS LA 10W-40 is recommend for the vehicles equipped with SCR or particulate filter system.

Benefits

- Protects engines against to wear at high speeds and high temperatures.
- It provides perfect protection and fuel economy under cold start-up conditions.
- It promotes the combustion efficiency and maximum power output by keeping the engine clean.
- It extends oil drain intervals.

Performance

API CI-4, ACEA E7-08, A3/B4-08, MB 228.3, MAN 3275, MTU TYPE 2, VOLVO VDS3, DEUTZ DQC-III

Typical Specifications*		
SAE Viscosity Grade		10W-40
Density, @ 15°C kg/m ³	ASTM 4052	0.873
Flash Point COC, °C	ASTM D 92	225
Kinematic Viscosity		
@ 40°C mm ² /s	ASTM D 445	100
@ 100°C mm ² /s		14.62
Viscosity Index	ASTM D 2270	149
Pour Point, °C	ASTM D 97	-36

* Values are changeable according to production.

