



maxima AUTO LPG 10W-40

High Performance Engine Oil

Description

A synthetic gasoline engine oil specially for the vehicles equipped with LPG systems.

Applications

Recommended for use in all high performance modern passenger cars, SUV and off-road vehicles.

Benefits

- It maintains the engine's manufacturing tolerances and minimizes the formation of residues by protecting the engine against wear at high temperatures.
- It yields the best fuel efficiency improves fuel economy and contributes to engine output.
- It provides more oxidation resistance and long service life compared with mineral oils.
- It keeps the engine clean and yields fuel efficiency.
- Helps protect the environment by lowering exhaust emission.
- It provides easy start-up.

Performance

API SL/CF, ACEA A3/B3, MB 229.1, VW 500.00/505.00

Typical Specifications*		
SAE Viscosity Grade		10W-40
Density, 15°C kg/lt	ASTM 4052	0.873
Flash Point, COC, °C	ASTM D-92	226
Kinematik Viskozite		
At 40°C, mm ² /s	ASTM D 445	91.18
At 100°C, mm ² /s		13.76
Viscosity Index	ASTM D 2270	154
Pour Point, °C	ASTM D 97	-33

* Values are changeable according to production.

Packing	
Plastic	1 lt, 4 lt
Drum	180 kg

