



## MAXIMUS LA 10W-40

### New Generation Synthetic Diesel Engine Oil for EURO 3/4 Vehicles

#### Description

Produced to ensure perfect lubrication of especially the modern heavy-duty diesel engines of EURO 4 norm equipped with a particle filter and diesel engines of EURO 3 and EURO 4 norms equipped with an SCR system. Thanks to the low-ash additives it contains, it ensures superior engine protection and longer oil change intervals.

#### Performance

API CF, ACEA E6/E4  
MB 228.5/MB 228.51  
MAN 3277 low ash, MAN 3477  
MTU MTL 5044 TYP3, RVI RXD

#### Typical Specifications\*

SAE Viscosity Grade		10W-40
Density, @ 15°C g/ml	ASTM 4052	0.86
Flash Point, COC, °C	ASTM D 92	237
Kinematic Viscosity		
at 40°C mm <sup>2</sup> /s	ASTM D 445	95.0
at 100°C mm <sup>2</sup> /s		14.4
Viscosity Index	ASTM D 2270	166
Pour Point, °C	ASTM D 97	-33

\* Values are changeable according to production.

#### Packing

Plastic Bottles	7 lt, 17.5 kg
Tin	16 kg
Drum	175.3 kg



[www.petrolofisi.com.tr](http://www.petrolofisi.com.tr)  
e-mail: [madeniyag@poas.com.tr](mailto:madeniyag@poas.com.tr)  
Customer Information Line: 0 800 211 02 29

