

MAXIMA 10W-30

Fully Synthetic Engine Oil

Definition

It is a high performance synthetic engine oil formulated with the addition of advanced technology additives to high quality synthetic base oils.

Places of Use

Recommended for high performance modern vehicles, passenger cars, gasoline and diesel engines, suv and off-road vehicles, 4x4 off-road vehicles such as CHRYSLER, GMC, FORD, DODGE, TOYOTA, NISSAN or pick ups.

Features and Benefits

- Provides maximum fuel saving, keeps the engine clean.
- Provides longer oil change interval.
- Increases efficiency by reducing friction inside the engine.
- Even under heavy conditions, thanks to its balanced viscosity, it prevents tearing of oil and provides protection.

Specifications and Approvals

API SL / CF, ACEA A3 / B4, VW 501.01 / 505.00

Typical Features *

SAE Viscosity Grade		10W-30
Density, @ 15 ° C, kg / m ³ Flash	ASTM D-4052	0.874
Point, COC, ° C Viscosity, 40 ° C,	ASTM D-92	220
mm ² / s Viscosity, 100 ° C, mm ² /	ASTM D 445	62
s Viscosity Index		9,8
	ASTM D-2270	141
Pour Point, ° C	ASTM D-97	- 24

* Values may differ from production to production.