MAXIGEAR EP-X 85W-140

High Quality Automotive Gear Oil

Definition

MAXIGEAR EP-X 85W-140 is an automotive gear oil developed for the differentials of heavy vehicles.

Places of Use

MAXIGEAR EP-X 85W-140 is used in differentials of heavy vehicles requiring API GL-5 level.

Features and Benefits

- Protects the components.
- Provides long oil change interval, protects parts from excessive and sudden loads.
- Provides maximum protection by preventing thinning of the film layer, provides effective protection even at the lowest temperatures.
- It protects components perfectly even at low temperatures and long time intervals.
- Provides fuel economy and reduces operating costs.
- It prevents oil thickening, formation of deposits and harmful acidic chemicals.
- Protects components and prevents oil leaks.

Specifications and Approvals

API GL-5, MIL-L-2105D

Typical Features *

SAE Viscosity Grade		85W-140
Density, @ 15 ° C, kg / m³ Flash	ASTM D-4052	0.910
Point, COC, ° C Viscosity, 40 ° C,	ASTM D-92	220
mm² / s Viscosity, 100 ° C, mm² /	ASTM D-445	347
s Viscosity Index	7.6.12 1.10	25,6
	ASTM D-2270	97
Pour Point, ° C	ASTM D- 97	- 15

^{*} Values may differ from production to production.

