



## MAXIGEAR S 75W-80

### Synthetic Long-Life Gear Box Oil

#### Description

Maxigear S 75W-80 is a high performance all seasons extreme pressure synthetic gear oil developed in particular for buses and heavy duty vehicles with ZF gear box.

#### Applications

Maxigear S 75W-80, is developed for buses and commercial vehicles operating under extremely heavy duty, where particularly long oil change intervals are recommended, for use in ZF gear boxes with or without interarder systems.

#### Benefits

- Very good aging resistance provides a long life between oil changes.
- Very high protection against corrosion.
- Excellent lubrication and wear prevention.
- Super extreme pressure characteristics.
- Perfect temperature-viscosity compatibility ensured with the smart oil technology.
- Very low pour point reduces wear at initial operation, and provides fuel savings.

#### Performance

API GL-4, MIL-L-2105, MAN 341 Typ. Z3, ZF TE-ML 02D

Typical Specifications*		
SAE Viscosity Category		75W-80
Density, @ 15°C g/ml	ASTM 4052	0.883
Flash Point COC, °C	ASTM D 92	230
Kinematical Viscosity		
@ 40°C mm <sup>2</sup> /s	ASTM D 445	66
@ 100° mm <sup>2</sup> /s		9.6
Viscosity Index	ASTM D 2270	130
Pour Point, °C	ASTM D 97	-39

\* Values may differ slightly between manufacturing parties.

